





ステンレスバンドを使ってクレードルなどを装着する前に、まずバンドのみを支柱に仮組みして、正しく取り付けられるよう準備をしてください。



ステンレスバンドはあらかじめ支柱と同じ径のパイプを使って形を整えてありますが、輸送中の衝撃などで変形してしまっている場合があります。

ステンレスバンドを支柱に巻き付けたとき、バンドの両端がぴったりと重なり合い、さらにナットがボルトの延長線に対して直角になるよう、バンド端の曲げ角度を手で調整してください。

この作業を行わない場合の取り付けは保証できません。ご注意ください。



バンド端がぴったりと重なっていない場合、特にナット側が曲がっているとボルトは正しくねじ込めません。ボルトが途中で止まってしまうのは、ナットに対して斜めにねじ込んでしまっているためです。

ボルトは少なくとも3回転以上は指でねじ込んでいき、工具はそれ以降の最終的な締め付けのみ使用してください。最初から工具を使用しないこと。

お問い合わせ先


株式会社 箕浦 カスタマーサービス

〒503-2305 岐阜県安八郡神戸町神戸 1197-1

Phone (0584) 27-3132 / Fax (0584) 27-4258

infodesk@minoura.jp / www.minoura.jp




Prior to installing the bike cradle with using the stainless band, try to check if the band is in proper shape by temporarily assembling the band alone to the pillar.



The supplied stainless band is pre-formed in the factory by using the same diameter tube. However, it may be deformed due to the rough handling or heavy shock during shipment. So checking the band shape is crucial.

Check if both band ends are fully overlapping each other without any clearance and the nut is set at exactly right angle to the bolt.

If not, bend the band end manually to adjust the band shape properly.



If the band end angle is not correct, you should not be able to screw the bolt properly.

If the bolt has been stuck in the beginning of screwing, the bolt is not set straight, but angled.

Be sure you turn the bolt manually at least 3 revolutions, then use your tool. Do not use tool from the beginning.

Contact

Minoura Japan Headquarters

1197-1 Godo, Anpachi, Gifu 503-2305 Japan

Phone +81-584-27-3131 / Fax +81-584-27-7505

minoura@minoura.jp / www.minoura.jp